

technical data sheet

PennWhite Ltd, Aston Way, Midpoint 18 Business Park, Middlewich, Cheshire, CW10 0HS

Description

FoamDoctor® G2898 is a foam control agent based on hydrocarbons and non-ionic surfactants.

Applications

FoamDoctor® G2898 is formulated to control unwanted foam in a number of applications where foaming is an inherent problem such as the manufacture of water based paint, latex, inks, coatings and emulsion polymerisation. FoamDoctor® G2898 can also be used in metalworking applications including cutting oil formulations.

Product Features

FoamDoctor® G2898 is 100% active.

Method of Use

FoamDoctor® G2898 can be used as supplied or pre-diluted in water. Dosage will depend on the application and should be established by trial. When used in paint manufacture 0.2 – 0.5 % of FoamDoctor® G2898 is recommended and can be split between the pre-grinding and the let-down stage. For adhesive manufacture 0.5 – 1 % of FoamDoctor® G2898 based upon the weight of latex solids is usually adequate.

Product Safety

A Safety Data Sheet compliant with EU 2015/830 is available for FoamDoctor® G2898 on request. It contains any safe handling guidelines that may be relevant to this product.

Storage, Shelf Life & Packaging

FoamDoctor® G2898 has a shelf life of 24 months when stored in original and unopened containers between 5°C and 30°C. Slight sedimentation may occur during storage and it is essential that the product is stirred thoroughly before use. This product is typically available in 25, 220 and 1,000 litre containers. Please note that it is sold in kilograms and the actual capacity of a container (in kg) is dependent upon the specific gravity of its contents.

Typical Properties

- Appearance: Opaque yellow tan liquid
- Specific Gravity: 0.85 – 0.90 g/ml
- Viscosity: 200 – 1000 cP
- pH: 6.0 – 8.0

Please note; these are typical properties only and should NOT be construed or used as a specification for this product.

(OPM3/D3)

TDS: 068

Issue: 10

Revised: 20/06/2023

Page 1 of 1



This product is manufactured in a facility whose Quality Management System is certified as being in conformity with ISO 9001:2015 by Intertek Certification Ltd.



This product is manufactured in a facility which operates in line with the Chemical Business Association's Responsible Care program.

Technical Support Contact Details

Telephone: +44 (0)1606 734820

Email: info@pennwhite.co.uk

Website: www.pennwhite.co.uk