

technical data sheet

PennWhite Ltd, Aston Way, Midpoint 18 Business Park, Middlewich, Cheshire, CW10 0HS

Description

Proverlube Base 2 is a wet film mineral oil based synthetic lubricant.

Applications

Proverlube Base 2 is formulated to provide effective lubrication in the high temperature and high humidity environment inside commercial proving ovens. It is particularly suitable for use with oven chains.

Product Features

Proverlube Base 2 does not carbonise or form gummy deposits even when exposed to temperatures up to 200°C

Method of Use

Proverlube Base 2 should be applied to the item to be lubricated by standard lubricators, brushes or dipping.

Toxicity & Handling

Proverlube Base 2 is not classed as hazardous under current CLP regulations. Full details are available in the applicable Safety Data Sheet.

Storage, Shelf Life & Packaging

Proverlube Base 2 has a shelf life of 24 months when stored in original and unopened containers between 5°C and 30°C. It is available in 25kg, 200kg and 1,000kg packs.

Typical Properties

- TBC To be confirmed

Please note; these are typical properties only and should NOT be construed or used as a specification for this product.

(OPM3/D3)

TDS: 150

Issue: 05

Revised: 03/09/2018

Page 1 of 1



This product is manufactured in a facility whose Quality Management System is certified as being in conformity with ISO 9001:2015.



This product is manufactured in a facility which operates in line with the Chemical Business Association's Responsible Care program.

Technical Support Contact Details

Telephone: +44 (0)1606 734820

Fax: +44 (0)1606 837867

Email: info@pennwhite.co.uk

Website: www.pennwhite.co.uk